

S-5![®]

The Right Way

GRIPPERFIX[®]

Roof-mounted utilities, such as split system condensing units, duct supports, communication equipment and service walkways can support a building envelope or compromise it. The S-5! GRIPPERFIX system, with S-5! clamps and brackets is *The Right Way*[™] to mount to any metal roof using our lifetime "double-seal" performance – or no roof penetration at all. GRIPPERFIX is quick and simple to install, preserves warranties and lasts the life of the roof.

Don't leave it to chance: Fix it, so it never needs "fixing." S-5! affordable mounting products ensure secure and dependable attachment that preserves the integrity of the roof and avoids destructive algae corrosion, leaks or rust. Done once – the right way – It's ripper!

The right way to attach almost anything to metal roofs!

The Wrong Way



The Right Way[™]



Features:

- No penetration of concealed-fix roof
- Factory double-seal for pierce-fix roof
- No field-applied sealants needed
- Eliminates corrosion, rust and algae
- All aluminium & stainless
- Limited lifetime materials & workmanship warranty*
- AND lower cost than the wrong way!




www.S-5.com |

*Visit website for details.



Use this detail for profiles such as KLIP-LOK[®], Speed Deck Ultra[®]



Use this detail with profiles such as TRIMDEK[®]

Concealed-Fix Roof System

The rail, S-5! clamp and concealed-fix tabs are all that are needed. Just slide the tab into the strut and fix to the top of the clamp (bolts provided). This system is suitable for KLIPLOC[®] and Speed Deck Ultra[®] profiles. The most commonly used S-5! clamp for these profiles is the S-5-K Grip. Pads for vibration reduction/leveling and other mounting hardware are also available.

- Does not damage the roof system
- No holes; penetration-free attachment
- Free flow of rainwater under the system; no capillary entrapment
- Load distribution over a minimum of 8 bearing points (panel ribs)

Pierce-Fix (Exposed-Fix) Roof System

The rail and pierce-fix tabs are all that are needed. The tab slides into the strut and fixes to the rib (self-piercing screws provided). **GRIPPERFIX** strut is compatible with TRIMDEK[®] and other pierce-fix roofs. Pads for vibration reduction/leveling and other mounting hardware are also available.

- Self-piercing fasteners results in no drilling, swarf or rust
- Exclusive EPDM factory "double-seal"
- Free flow of rainwater under the system; no capillary entrapment
- Load distribution over minimum of 8 bearing points (panel ribs)

In order to customize the system to your roof, S-5!-GRIPPERFIX components are sold separately.

S-5![®] Warning! Please use this product responsibly!

The independent lab test data found at www.S-5.com can be used for load-critical designs and applications.

Products are protected by multiple U.S. and foreign patents. For published data regarding holding strength, fastener torque, patents, and trademarks, visit the S-5! website at www.S-5.com. S-5! products are patent protected.

Copyright 2022, Metal Roof Innovations, Ltd. Version 072822

Distributed by: